

Residential Vinyl Siding

City of Prior Lake Requirements Updated 8/4/2005

This handout is a guide only and is not intended as a complete list of requirements.

A Building permit is required for the residing of residential dwelling and garages.

SUBMITTALS:

A complete	building	permit	application	indicating	the	siding	product	and	house	wrap
products.										

☐ An evaluation service report and manufacturer's specifications for house wrap product.

INSTALLATION:

☐ Each siding carton labeled indicating compliance with standard ASTM D 36		Each siding carton	labeled indicating	compliance with	standard ASTM D 36
--	--	--------------------	--------------------	-----------------	--------------------

	Vinyl	Siding	Attachment
--	-------	--------	------------

Nominal Thickness	Wood or wood structural panel	Fiberboard sheathing
(Inches)	sheathing	into stud
0.035"	0.120" nail	0.120" nail
	1-1/2"	2"
	Staple- 1-3/4"	Staple- 2-1/2"

- Approved corrosion-resistive flashing shall be provided in the exterior wall envelope in such a manner as to prevent entry of water into the wall cavity or penetration of water to the building structural framing components. The flashing shall extend to the surface of the exterior wall finish and shall be installed to prevent water from reentering the exterior wall envelope. Approved corrosion-resistant flashings shall be installed at all of the following locations:
 - 1. At top of all exterior window and door openings in such a manner as to be leak proof.
 - 2. At the intersection of chimneys or other masonry construction with frame or stucco walls, with projecting lips on both sides under stucco copings.
 - 3. Under and at the ends of masonry, wood, or metal copings and sills.
 - 4. Continuously above all projecting wood trim.
 - 5. Where exterior porches, decks, or stairs attach to a wall or floor assembly of wood-frame construction.
 - 6. At walls and roof intersections.
 - 7. At built-in gutters.
 - 8. Where exterior material meets in other than a vertical line.

INSPECTIONS:

1.	A weather resistive sheathing paper inspection including all flashing in place, before siding is applied.
2.	A final inspection is required when combustion air requirements per 7672.1200 Subp. (2) and siding are complete.
	It is the permit holder's responsibility to call for all required inspections.
	To arrange for inspection call 952.447.9850, between the hours of $8:00$ a.m. $-4:30$ p.m. Please have your permit number available when you call.